ROOM YOU

RoomYou 1 (RY1)




The ROOMYOU™ sensor is engineered to monitor indoor environments, promoting wellbeing and comfort. Its square design features real-time sensing capabilities for CO2, temperature, humidity, air pressure, and melanopic lux.

- Portability: Battery-powered for convenient use
- Display: E-Ink screen for clear visibility
- Measurement Interval: 5-minute measurement intervals
- Data Export: Option to export data for analysis

This sensor is an essential tool for ensuring optimal indoor conditions and complying with standards for wellbeing*.

Key characteristics	Shape: L75 * W70.52 * D25.5 mm		
co2	CO2 Range: 0 to 9999 ppm Resolution 1 ppm Accuracy ±(30 ppm + 3 % of reading)		
<u>n</u>	Temperature		
	Range: -40 to 125 °C		
	Resolution 0.1 °C		
	Accuracy ±0.2 °C		
	Relative humidity		
	Range: 0 to 100%		
	Resolution 1%		
	Accuracy ±2%		
↓	Atmospheric pressure		
≈≈	Range: 260 to 1260hPa		
	Resolution 0.5 hPa		
	Accuracy ±3%		
	Light		
<u>\(\tau_{\chi} \) \(\tau_{\chi} \) </u>	M-EDI (Melanopic		
	Equivalent Daylight		
	Illuminance)		
	Range: 350 to 1000nm		
	Channels: 8		
	Accuracy ±5%		





Example data export (.csv)

Time(DD/MM/Y YYY h:mm:ss A)	Carbon dioxide(ppm)	Tempe rature(°C)	Relative humidity(%)	Atmospheric pressure(hPa)	Melanopic Lux (M-EDI)
19/04/2024 11:47	520	26.4	74	998.6	200
19/04/2024 11:52	512	26.4	74	998.4	203
19/04/2024 11:57	520	26.4	74	998	205
19/04/2024 12:02	522	26.5	74	997.9	209
19/04/2024 12:07	532	26.5	74	997.8	213

General specifications

IP rating	IP20
Operating temperature	-10°C to 50 °C
Operating humidity	0 to 100 %
Weight	76 g (excl batteries)
	104 g (with batteries)
	172 g (with pack-
	aging, excl batteries)
Material	Polycarbonate
Packaging excl.	2 pcs AA alkaline
	batteries**
Compliance	CE, UKCA
EAN	8720299314399

*Relevant Standards ANSI/ASHRAE 62.1-2022, RESET grade A, WELL $v2^{\text{TM}}$

^{**}Please be aware that sensors are shipped without batteries. Each sensor requires two AA batteries.